

**Models with solid door
see A.051**



Model No.	ML0406GWU	ML0806GWU	ML1006GWU	ML1506GWU	ML3006GWU	ML3506GWU
Temperature range	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C	+2°C to +8°C
Forced air circulation	Yes	Yes	Yes	Yes	Yes	Yes
Defrost (automatic / manual)	automatic	automatic	automatic	automatic	automatic	automatic
Electronic controller	Yes	Yes	Yes	Yes	Yes	Yes
Digital display	Yes	Yes	Yes	Yes	Yes	Yes
Temperature alarm visual / audible	Yes	Yes	Yes	Yes	Yes	Yes
Excess and insufficient temp. alarm	Yes	Yes	Yes	Yes	Yes	Yes
Open door alarm	Yes	Yes	Yes	Yes	Yes	Yes
No-volt remote alarm	No	No	Yes	Yes	Yes	Yes
External finish	painted steel plate	painted steel plate	painted steel plate	painted steel plate	painted steel plate	painted steel plate
Colour	white	white	white	white	white	white
Lock	Yes	Yes	Yes	Yes	Yes	Yes
Door type	glass door	glass door	glass door	glass door	glass door	glass door
Door hinges	not changeable	changeable	changeable	changeable	changeable	changeable
Door seal	not changeable	changeable	changeable	changeable	changeable	changeable
Internal finish	plastic, white	plastic, white	plastic, white	plastic, white	plastic, white	plastic, white
Interior light	No	Yes	Yes	Yes	Yes	Yes
Spark free	No	No	No	No	No	No
Shelves (number)	2	2	2	3	5	6
Shelf positions (number)	5	2	4	6	12	14
Shelf size (mm) (WxDxH)	270x308x6	438x274x6	427x374x6	520x400x6	4: 500x385x6 1: 497x340x6	500x385x6
Wire baskets (number)	0	1	1	1	1	1
Optional drawer system	Yes	Yes	Yes	Yes	Yes	Yes
Adjustable feet (number & position)	No	No	1 front foot	2 front feet 2 rear rollers	2 front feet 2 rear rollers	2 front feet 2 rear rollers
Gross capacity (l)	41	82	107	151	273	353
Net capacity (l)	35	67	103	141	269	349
External width (mm)	379	502	495	595	595	595
External depth (mm)	500	540	620	635	660	660
Door open depth (mm)	810	976	1050	1165	1180	1180
External height (mm)	702	660	830	845	1565	1860
Internal dimensions (mm) (WxDxH)	245x310x400	419x320x540	403x400x700	500x450x705 step (DxH): 165x185	480x445x1382 step (DxH): 175x255	480x445x1682 step (DxH): 175x265
Product weight (kg)	25.5	30	36.5	42	68.5	79
Voltage supply	1/N/PE-230V 50Hz	1/N/PE-230V 50Hz	1/N/PE-230V 50Hz	1/N/PE-230V 50Hz	1/N/PE-230V 50Hz	1/N/PE-230V 50Hz
Packed width (mm)	700	700	700	700	700	700
Packed depth (mm)	750	750	750	750	750	750
Packed height (mm)	890	825	1000	1022	1735	2035
Packed weight (kg)	32.5	37	43.5	49	75.5	86
Refrigerant type CFC / HCFC free	R134a	R134a	R134a	R600a	R600a	R600a



Recommendations for additional storage sets can be found in our separate catalogue. Please ask for a personal fitting option.

